Armstrong Flooring - Sheet Vinyl

TABLE OF CONTENTS

Specification Details....2
Clauses....2
Scope....2
Homogeneous Vinyl Sheet - Accolade....2
Homogeneous Vinyl Sheet - Natralis....4
Homogeneous Vinyl Sheet - Lovora....5
Homogeneous Vinyl Sheet - Armalon....6
Heterogeneous Vinyl Flooring....6
Safety Vinyl - Safeguard....7
Wall Vinyl - Wallflex....9
Trim & Accessories....9
Surface Preparation....10
Adhesive....10
Co-operation....10
Workmanship....10
Delivery & Handling....11
Preparation....11
Installation....11
Completion....12
Cleaning and Maintenance....12
Performance and Compliance....12
Compliances....13

1 Specification Details

Trade Sections: Floor Coverings

Description:

Keywords: Floor Coverings, Armstrong, Armstong's, Commercial Textile Floor Coverings, floor finishes, Vinyl sheet flooring, Safety Vinyl, Wall Vinyl.

2 Clauses

2.1 Scope

Help Note:

For technical information on products to attach to this project, please visit https://productspec.co.nz/en/supplier/armstrong

SMARTSPEC

2.1.1 Scope

Supply and install the specified Floor Coverings from Armstrong Flooring NZ to the locations, layouts and details shown on the drawings, complete with all associated components and accessories. All aspects of this work shall be in complete accordance with the manufacturers' technical literature (check armstrongflooring.co.nz , or call 0800 449 649 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for the specified Floor Coverings and components from Armstrong Flooring NZ.

2.2 Homogeneous Vinyl Sheet - Accolade

2.2.1 Accolade Plus

Accolade Plus® is a high-performance homogeneous vinyl sheet manufactured in Australia and features a multi-chip colour visual and an embossed surface to help ongoing maintenance and longevity. Armstrong Flooring's Accolade Plus® provides a hygienic surface which is ideal for hygiene critical areas such as hospitals, healthcare and aged care flooring environments. It is also designed to withstand high traffic making it also suitable for hospitality, shopping centres, office and light industrial spaces.

- 2.0 mm thick sheets with PUR surface.
- Slip resistance P3 / R10
- Fire performance CRF ≥ 8–10.9 kW/m²; Smoke ≤ 750 %.min.
- Group classification: Group 3 for wall application
- Environmental certifications include Best Environmental Practice PVC, GreenTag Gold Plus, FloorScore certified, EPD available.
- Roll widths: 1.83 m × 20 m

Collection name:
Style name/number:
Colour name/number:
Dimensions:
Construction:
Backing:
Installation method/direction:
Application method:
Installed location:

2.2.2 Accolade Safe

Accolade Safe® is an innovative Australian made vinyl sheet floor offering ultimate safety without the compromise of silicone chips found in conventional slip resistant flooring. Featuring reduced aquaplaning while aiding slip resistance, Armstrong Flooring's Accolade Safe® is recommended in hospital, healthcare, aged care, hospitality, and light industrial environments.

- Thickness: 2.0 mm.

SMARTSPEC

- Slip resistance P4, R10
- Fire resistance: CRF ≥8–10.9 kW/m2; Smoke ≤750 %.min. Group 3 walls
- Environmental: Best Environmental Practise PVC, GreenTag Gold Plus, FloorScore Certified compliant with Green Building Council low VOC emission rates, EDP available
- Sizes: 1.83m x 20m

Collection name:
Style name/number:
Colour name/number:
Dimensions:
Construction:
Backing:
Installation method/direction:
Application method:
Installed location:

2.2.3 Accolade Foothold

Accolade Foothold® is a homogeneous vinyl sheet flooring that features aluminium oxide particles for added slip resistance, encapsulated in a polyurethane surface to aid maintenance, and provide additional resistance against staining. Armstrong Flooring's Accolade Foothold® is Australian made and recommended for use in wet barefoot areas, such as ensuites, baths and shower rooms within hospital, healthcare, aged care and education environments.

- Thickness: 2.0 mm.
- Slip resistance: Foothold P4, R11
- Fire resistance: CRF ≥8–10.9 kW/m2; Smoke ≤750 %.min. Group 3 walls
- Environmental: Best Environmental Practive PVC, GreenTag Gold Plus, FloorScore Certified, compliant with Green Building Council low VOC emission rates, EPD available
- Sizes: 1.83m x 20m

Collection name:
Style name/number:
Colour name/number:
Dimensions:
Construction:
Backing:
Installation method/direction:
Application method:
Installed location:

SMARTSPEC