BBS Timbers Flooring

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Timber Species 2
- Flooring Profile 3
- Substrate Sealer 4
- Adhesive & Fixings 5
- Samples 5
- Reserve Material 5
- Co-operation 5
- Workmanship 6
- Delivery and Handling 6
- Preparation 7
- Installation 10
- Applied Finish 13
- Temporary Protection 14
- Completion 14

Compliances 15

SMARTSPEC

1 Specification Details

Trade Sections: Carpentry, Floor Coverings
Description: This specification covers he timber flooring range for BBS timbers
Keywords: BBS Timber flooring t&g t+g tongue groove

2 Clauses

2.1 Scope

Help Note:
For further information, or in the situation of conflict or doubt, contact BBS Timbers Ltd on (website) http://bbstimbers.co.nz , (call) 0800 227 862, or (email) office@bbstimbers.co.nz

2.1.1 Scope

Supply and install Timber Flooring from BBS Timber as specified herein, complete with all accessories and trim, to the areas identified on the drawings. All aspects of this work shall be in complete accordance with BBS Timber Flooring installation requirements and technical literature, (check BBS Timber Flooring website, email: office@bbstimbers.co.nz, or call 0800 227 862 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for the specified Timber Flooring from BBS Timber.

2.2 Timber Species

Help Note:
For further information, or in the situation of conflict or doubt, contact BBS Timbers Ltd on (website) http://bbstimbers.co.nz , (call) 0800 227 862, or (email) office@bbstimbers.co.nz

2.2.1 American White Oak

Solid Flooring shall be manufactured from American White Oak (*Quercus Alba*), Prime grade, kiln-dried solid hardwood.

2.2.2 American Hard Maple

Solid Flooring shall be manufactured from American Hard Maple, kiln-dried solid hardwood.

2.2.3 American Walnut

Solid Flooring shall be manufactured from American Walnut, kiln-dried solid hardwood.

2.2.4 French Chestnut

Solid Flooring shall be manufactured from French Chestnut, kiln-dried solid hardwood.

2.2.5 French Oak

Solid Flooring shall be manufactured from French Oak, kiln-dried solid hardwood.

SMARTSPEC

2.2.6 Jarrah

Solid Flooring shall be manufactured from Jarrah, kiln-dried solid hardwood.

2.2.7 Jatoba

Solid Flooring shall be manufactured from Jatoba, kiln-dried solid hardwood.

2.2.8 Kwila

Solid Flooring shall be manufactured from Kwila, kiln-dried solid hardwood.

2.2.9 Matai

Solid Flooring shall be manufactured from Matai, kiln-dried solid hardwood.

2.2.10 Rimu

Solid Flooring shall be manufactured from Rimu kiln-dried solid hardwood.

2.2.11 Garapa

Solid Flooring shall be manufactured from Garapa, kiln-dried solid hardwood.

2.2.12 Rosewood

Solid Flooring shall be manufactured from Rosewood, kiln-dried solid hardwood.

2.2.13 Eucalyptus Saligna

Solid Flooring shall be manufactured from Eucalyptus Saligna, kiln-dried solid hardwood.

2.2.14 Spotted Gum

Solid Flooring shall be manufactured from Spotted Gum, kiln-dried solid hardwood.

2.2.15 Tawa

Solid Flooring shall be manufactured from Tawa, kiln-dried solid hardwood.

2.2.16 Victorian Ash

Solid Flooring shall be manufactured from Victorian Ash, kiln-dried solid hardwood.

2.3 Flooring Profile

Help Note:

For further information, or in the situation of conflict or doubt, contact BBS Timbers Ltd on (website) http://bbstimbers.co.nz , (call) 0800 227 862, or (email) office@bbstimbers.co.nz

2.3.1 BBS 8513 FL (Overlay) 85mm x 13mm - Solid Flooring

Solid Flooring Profile: BBS 8513 FL (Overlay) 85mm x 13mm thick, T&G timber strip overlay, end-matched flooring. Installed in accordance with the manufacturer's requirements to the locations and details shown on the drawings.

Installed Location: