Dimond Profiled Metal Roofing

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Corrugated Roofing 4
- Trapezoidal Roofing 6
- Concealed Clip Roofing 20
- Eurotray® Roofing 27
- Roofing Material 39
- Ancillary Components & Accessories 86
- Co-operation 88
- Workmanship 89
- Delivery & Handling 89
- Preparation 90
- Installation 91
- Fixing 93
- Completion 112

Compliances 113

SMARTSPEC

1 Specification Details

Trade Sections: Roofing
Description:
Keywords: Roofing, Dimond, Dimond Profiled Metal Roofing, longrun roofing, long-run roofing, long run metal roofing, long-run metal roofing, longrun metal roof cladding, long-run metal roof cladding, profiled longrun roofing, profiled long-run roofing, roof cladding, profiled metal, profile metal, profiled steel, profile steel, profiled metal cladding, profiled metal roofing, profile metal roof cladding, profile metal roofing, metal roofing, metal cladding, prepainted roofing, pre-painted roofing, prepainted roof cladding, pre-painted roof cladding, prefinished roofing, pre-finished roofing, prefinished roof cladding, pre-finished roof cladding, precoated roofing, pre-coated roofing, precoated roof cladding, pre-coated roof cladding, prepainted steel, pre-painted steel, prefinished steel pre-finished steel, precoated steel, pre-coated steel, coated steel, prepainted metal, pre-painted metal, prefinished metal, pre-finished metal, precoated metal, pre-coated metal, coated metal, roll formed roofing, roll formed cladding, roll formed steel roofing, roll formed steel cladding, roll formed metal roofing, roll formed metal cladding, corrugated roofing, trapezoidal roofing, trough roofing, tray roofing, fully supported metal roofing, 0.4mm BMT, 0.55mm BMT, BMT, bmt, (BMT), base metal thickness, G550 steel, G300 steel, rainwater catchment, rainwater run-off, rainwater run off, run-off, run off, Colorsteel, Colorsteel Endura, Colorsteel Maxx, Colorcote, Colorcote ZM8, ZM8, ZMX, ZR8, ZRX, ARX, AR8, Zincalume, GALVSTEEL®, galvanised steel roofing, Corrugate, Dimond Corrugate, Styleline, Dimond Styleline, Dimondek 300, Dimond Dimondek 300, Dimondek 400, Dimond Dimondek 400, V-Rib, Dimond V-Rib, vrib,

2 Clauses

2.1 Scope

Help Note:
This section covers profiled metal roofing from Dimond Roofing. Profiles are listed in clause sections according to type - Corrugated Roofing, Trapezoidal Roofing, Concealed Clip Roofing, Eurotray® Roofing.

Select the appropriate Environmental Category in which the project is situated. Check the Project Details 'Exposure Zone' category is set to the correct zone.

Inland Moderate (ISO 9223 Category: C2): Characterised by no obvious marine influences. Typically more than 1000 metres from the exposed coasts or more than 500 metres from industrial emissions.

SWARTSPEC

Coastal Moderate (ISO 9223 Category: C3): Characterised by light salt deposits, a frequent smell of salt in the air. Typically within 500 metres to 1km from breaking surf or in the immediate vicinity of calm salt water such as estuaries.

Coastal Severe (ISO 9223 Category: C4): Characterised by light salt deposits, a frequent smell of salt in the air. Typically commencing from Very Severe Zone up to 500 metres or more inland from breaking surf; or in the immediate vicinity of calm salt water such as harbour foreshores.

Coastal Very Severe Zone (ISO 9223 Category: C5M): Characterised by heavy salt deposits, an almost constant smell of salt spray in the air. Typically within 50-100 metres from breaking surf on East Coast, 100 - 200 metres from breaking surf on West Coast.

Industrial Very Severe Zone (ISO 9223 Category: C5I): Characterised by industrial areas with high humidity and aggressive atmospheres.

For further information and technical advice, call Dimond Roofing on 0800 766 377, or email roofspec@dimond.co.nz.

For technical information on products to attach to this project, please visit productspec.co.nz/en/supplier/dimond%20roofing.

2.1.1 Inland Moderate (ISO 9223 Category: C2)

Supply and install the specified Dimond Profiled Metal Roofing to the locations identified on the drawings, complete with all accessories. All aspects of this work shall be in complete accordance with the Dimond Roofing & Cladding Systems Manual and other relevant Dimond technical literature (check www.dimond.co.nz, or call 0800 346 663 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Dimond Profiled Metal Roofing.

2.1.2 Coastal Moderate (ISO 9223 Category: C3)

Supply and install the specified Dimond Profiled Metal Roofing to the locations identified on the drawings, complete with all accessories. All aspects of this work shall be in complete accordance with the Dimond Roofing & Cladding Systems Manual and other relevant Dimond technical literature (check www.dimond.co.nz, or call 0800 346 663 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Dimond Profiled Metal Roofing.

2.1.3 Coastal Severe (ISO 9223 Category: C4)

Supply and install the specified Dimond Profiled Metal Roofing to the locations identified on the drawings, complete with all accessories. All aspects of this work shall be in complete accordance with the Dimond Roofing & Cladding Systems Manual and other relevant Dimond technical literature (check www.dimond.co.nz, or call 0800 346 663 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.