Polyflor Commercial LVT

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Commercial LVT 2
- Resilient Flooring 3
- Commercial Wall & Ceiling Covering 9
- Low or Intermittent Use LVT 10
- Trim & Accessories 11
- Underlayment 12
- Levelling Patch Compounds 12
- Primer 13
- Adhesive 14
- Sample 15
- Reserve Material 16
- Co-operation 16
- Workmanship 16
- Delivery & Handling 16
- Preparation 17
- Installation 20
- Completion 23

Compliances 23

SMARTSPEC

1 Specification Details

Trade Sections: Floor Coverings
Description: Commercial Luxury Vinyl Tile - from Polyflor, Floor covering, Resilient Flooring, Acoustic Flooring, Wall - Ceiling, Screed & Adhesives.
Keywords: Polyflor, Floor covering, Resilient Flooring, Acoustic Flooring, Wall - Ceiling, Screed & Adhesives. Okatmos Servoplan Servofine Affinity Polyclad Finesse Polyflor Sport 67, Polysafe, Polysafe Vogue, Polysafe Verona, Quattro, Expona, Bloc, Acoustix, Palettone, Prestige, Wovon, Expona, Commercial Luxury Vinyl Tile

2 Clauses

2.1 Scope

Help Note:
For technical enquiries contact Polyflor on 0800765935 or e-mail sales@polyflor.co.nz or head to the website www.polyflor.co.nz

2.1.1 Scope

Supply and install the specified Commercial Vinyl Surfacing from Polyflor to the locations, layouts and details shown on the drawings, complete with all associated components and accessories. All aspects of this work shall be in complete accordance with the manufacturers' technical literature (check www.polyflor.co.nz, or call 0800 765 935 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.
No substitutions are permitted for the specified Commercial Vinyl Surfacing from Polyflor.

2.2 Commercial LVT

Help Note:
For technical enquiries contact Polyflor on 0800 765 935 or e-mail sales@polyflor.co.nz or head to the website www.polyflor.co.nz

2.2.1 Expona Commercial

Expona Commercial floor covering standard E649 EN ISO 23997 PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.
Installed in accordance with the manufacturer's installation requirements and NZS/AS 1884, to the locations and layout shown on the drawings.
Gauge: 2.5mm
Wear Layer: 0.55mm
Plank size: 36@ 101.6x914.4mm, 24 @ 152.4x914.4mm 18 @ 154.4x1219.2mm, 15 @ 184.2x1219.2mm 14 @ 203.2x1219.2mm, 12 @ 184.2x1524mm, 12 @ 76.2x914.4mm, 12 @

101.6x914mm, 12 @ 152.4x914.4mm
Packaging Plank Size: 12 @ 304.8x914.4mm, 11 @ 203.2x1524mm, 9 @ 609.6x609.6mm, 8 @ 457.2x914.4mm, 12 @ 152.4x609.6mm, 12 @ 304.8x304.8mm, 6 @ 304.8x609.6mm
Colour: 17 Shades
Slip resistance: DIN 51130 R10, EN 13893 DS, AS 4586 R10
Reaction to fire: EN 13501-1 Bfl – s1
Underfloor heating: EN 12664-2 Suitable, max 27°C

Colour:
Installed location:

2.2.2 Expona Simplay

Expona Simplay floor covering standard E649 EN ISO 23997 heterogeneous, PVC.
Installed in accordance with the manufacturer's installation requirements and NZS/AS 1884, to the locations and layout shown on the drawings.
Gauge: 5mm
Wear Layer: 0.7mm
Plank size: 10 @ 177.8x1219.2, 8 @ 185x1505
Packaging Plank Size: 10@ 177.8x1219.2, 10 @ 304.8x609.6, 6@ 600x600, 4@ 914.4x914.4
Colour: 17 Shades
Slip resistance: DIN 51130 R10, EN 13893 DS, AS 4586 R10
Reaction to fire: EN 13501-1 Bfl – s1
Underfloor heating: EN 12664-2 Suitable, max 27°C

Colour:
Installed location:

2.3 Resilient Flooring

Help Note:
For technical enquiries contact Polyflor on 0800 765 935 or e-mail sales@polyflor.co.nz or head to the website www.polyflor.co.nz

2.3.1 Classic Mystique PUR

Classic Mystique PUR Heavy duty, homogeneous floor coverings.
Installed in accordance with the manufacturer's installation requirements and NZS/AS 1884, to the locations and layout shown on the drawings.
Gauge: 2mm
Wear Layer: 2mm
Roll size: 2mx20m
Tile size: 300x300mm, 608x608mm
Colour: 24 Shades
Slip resistance: DIN 51130 R9, EN 13893 DS, AS 4586 R9
Reaction to fire: EN 13501-1 Bfl – s1, ASTM E662 <450, ASTM E648 Class 1, BCA Spec CIJO Clause 3.
Underfloor heating: EN 12664-2 Suitable, max 27°C