JSC Hardwood Decking

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Species 2
- Profile & Fixing 3
- Anti-Slip Protection 4
- Co-operation 4
- Preparation 5
- Installation 5
- Completion 5

Compliances 5

SWARTSPEC

1 Specification Details

Trade Sections: Carpentry, Landscaping
Description:
Keywords: Carpentry, JSC Timber, hardwood timber, hardwood decks, hardwood decking, decks, decking, timber decks, timber decking,wooden decks, wooden decking, wood decking,
solid hardwood, solid hardwood decks, solid hardwood decking, timber species, hardwood species, wood species, Garapa, Kwila, Pacific Jarrah, Jarrah, Purpleheart, Vitex, grip tread, grip-tread, grip tread decking, grip-tread decking, profiled decking, profiled timber decking, profiled hardwood decking,

2 Clauses

2.1 Scope

Help Note:
For technical information on products to attach to this project, please visit productspec.co.nz/en/supplier/jsc%20timber.

2.1.1 Scope

Supply and install the selected JSC Hardwood Decking to the areas identified on the drawings, complete with all accessories and trim. All aspects of this work shall be in complete accordance with JSC Ltd Hardwood Decking installation instructions, (check www.jsc.co.nz, or call 09 412 2800 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

2.2 Species

2.2.1 Garapa

Garapa, FSC™ certified solid hardwood.

2.2.2 Kwila

Kwila, VLO and FLC-TLTV certified hardwood.

2.2.3 Purpleheart

Purpleheart, 2nd Party (Governmental) Forestry Management certified solid hardwood.

2.2.4 Vitex

Vitex, Non-Controversial "Community Timber" certified solid hardwood.

SMARTSPEC

2.2.5 Iroko

Iroko, VLC-TLTV certified solid hardwood.

2.3 Profile & Fixing

Help Note:
JSC offer a range of decking profiles in options that include standard and architectural finishes. Please check the availability and lead times specific to your profile. These can be confirmed by contacting JSC on 09 412 2800.

2.3.1 65mm x 19mm - Smooth Finish

65mm wide x 19mm thick, Smooth finish. Fixed with 65mm long stainless steel decking screws. JSC advocates that all hardwood decking is fixed with screws. If nail fixed, fix with stainless steel annular grooved nails of sufficient length.

Please check the availability and lead time for the selected profile by contacting JSC on 09 412 2800.

2.3.2 90mm x 19mm - Smooth Finish

90mm wide x 19mm thick, Smooth finish. Fixed with 65mm long stainless steel decking screws. JSC advocates that all hardwood decking is fixed with screws. If nail fixed, fix with stainless steel annular grooved nails of sufficient length.

Please check the availability and lead time for the selected profile by contacting JSC on 09 412 2800.

2.3.3 90mm x 19mm - Grip Tread Finish

90mm wide x 19mm thick, Grip Tread finish. Fixed with 65mm long stainless steel decking screws. JSC advocates that all hardwood decking is fixed with screws. If nail fixed, fix with stainless steel annular grooved nails of sufficient length.

Please check the availability and lead time for the selected profile by contacting JSC on 09 412 2800.

2.3.4 115mm x 19mm - Smooth Finish

115mm wide x 19mm thick, Smooth finish. Fixed with 65mm long stainless steel decking screws. JSC advocates that all hardwood decking is fixed with screws. If nail fixed, fix with stainless steel annular grooved nails of sufficient length.

Please check the availability and lead time for the selected profile by contacting JSC on 09 412 2800.

2.3.5 140mm x 19mm - Smooth Finish

140mm wide x 19mm thick, Smooth finish. Fixed with 65mm long stainless steel decking screws. It is essential that decking 140mm or wider is fixed with screws.

Please check the availability and lead time for the selected profile by contacting JSC on 09 412 2800.

SMARTSPEC