Dominator Garage Doors

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Residential Rolling Doors 2
- Residential Sectional Doors 3
- Insulated Sectional Doors 9
- Industrial Rolling Doors 12
- Door Material & Colour 14
- Door Opener 19
- Co-operation 21
- Workmanship 21
- Delivery & Handling 22
- Preparation 22
- Installation 22
- Completion 23

Compliances 23

SMARTSPEC

1 Specification Details

Trade Sections: Specialist Services & Equipment
Description:
Keywords: Specialist Services & Equipment, B & D Doors, B&D Doors, Dominator Garage Doors, roller garage doors, sectional garage doors, tilt garage doors, door openers, garage door openers, Dominator Roller Door Series A, Flex-A-Door, Nevada Negative Detail Sectional Door, NatureSteel Sectional Door, Somerset Sectional Door, Sierra Sectional Door, Milano Sectional Door, Valero Sectional Door, Georgian Sectional Door, Estate Sectional Door, Futura Sectional Door, Horizontal Cedar Sectional Door, insulated sectional doors, insulated garage doors, Dominator Roller Door Series A Mini Warehouse, Dominator Roller Door Series B Semi-Industrial, Dominator Roller Door Series C Industrial, residential garage doors, industrial garage doors, industrial roller doors, semi-industrial roller doors, semi industrial roller doors, roller garage door openers, sectional garage door openers, Dominator GDO-6 Roller Door Opener, Dominator GDO-11 Door Opener, Dominator GDO-9 Sectional Door Opener, Dominator GDO-11 Sectional Door Opener, Dominator GDO-10 Roller Door Opener, heavy-duty roller door openers

2 Clauses

2.1 Scope

Help Note:
For technical information on products to attach to this project, please visit productspec.co.nz/en/supplier/garador%20garage%20doors.

2.1.1 Scope

Supply, install, and commission the selected Dominator Garage Doors to the locations identified on the drawings, complete with all accessories for proper installation and system operation. All aspects of this work shall be in strict accordance with the manufacturer's technical literature and installation requirements (check www.dominator.co.nz, or call 03 384 5145 for the latest editions), other relevant product manufacturers' recommendations, and as noted and detailed on the drawings.

No substitutions are permitted for Dominator Garage Doors.

2.2 Residential Rolling Doors

2.2.1 Dominator Roller Door - 'Series A'

Dominator Roller Door - 'Series A'. Traditional metal roller door for residential applications.
Roller Curtain: manufactured from Zincalume®, or COLORSTEEL® break-pressed continuous steel sheet - colour as specified.

SMARTSPEC

Door Guides: Roll-A-Guides; galvanised steel silenced guides with full length Nylofelt® running strips.
Weather Seal: deep cushioning neoprene weather strip.
Opening operation: manual or automatic (as specified). External locking for manual doors.

Face mounted roller door installation, fastened to the interior face of the wall opening.
Door opening (daylight) height: from 1300mm, up to 3200mm.
Door opening (daylight) width: from 1250mm, up to 3200mm.
Headroom clearance from base of lintel: minimum 400mm.
Sideroom clearance: minimum 80mm for manual operation; minimum 135mm for automatic operation.
Drive through clearance height: 70mm below base of the lintel.

Manufactured and installed in accordance with AS/NZS 4505 and the manufacturer's requirements, to the locations, dimensions, and details as scheduled and shown on the drawings.

Location:

2.2.2 Dominator Flex-A-Door

Dominator Flex-A-Door. Suitable for installations with restricted headroom. The Flex-A-Door curtain opens upwards, on a curved overhead track, into a horizintal position (not around a drum) - similar to a sectional door.
Roller Curtain: Roll-A-Door curtain; manufactured from COLORSTEEL® break-pressed continuous steel sheet - colour as specified.
Door Guides: Roll-A-Guides; galvanised steel silenced guides with full length Nylofelt® running strips.
Weather Seal: deep cushioning neoprene weather strip.
Opening operation: manual or automatic (as specified).

Face mounted installation - installed against the interior face of the wall.
Door opening (daylight) height: up to 2775mm.
Door opening (daylight) width: from 1200mm, up to 3150mm.
Headroom clearance - manual operation: minimum 80mm from ceiling.
Headroom clearance - automated operation (with C-rail): minimum 130mm from ceiling.
Sideroom clearance: minimum 100mm.
Drive through clearance height (below top of opening): 40mm for manual operation, 60mm for automated operation.

Manufactured and installed in accordance with AS/NZS 4505 and the manufacturer's requirements, to the locations, dimensions, and details as scheduled and shown on the drawings.

Location:

2.3 Residential Sectional Doors

Help Note:
Includes Steel sectional doors and Timber (Cedar) sectional doors.