Pink Batts Insulation

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Requirements 3
- Underfloor Thermal Insulation 3
- Wall Thermal Insulation 5
- Ceiling Thermal Insulation 12
- Building Insulation Blanket (BIB) 22
- Acoustic Insulation 26
- Co-operation 27
- Workmanship 27
- Delivery & Handling 28
- Installation 28
- Completion 34

Compliances 34

SMARTSPEC

1 Specification Details

Trade Sections: Insulation

Description:

Keywords: Insulation, Tasman Insulation, Pink Batts, thermal insulation, acoustic insulation, glasswool insulation, insulation segments, insulation blanket, building insulating blanket, BIB, under floor insulation, floor insulation, floor cavity insulation, interfloor insulation, inter-floor insulation, interstorey insulation, inter-storey insulation, wall insulation, wall cavity insulation, external wall insulation, internal wall insulation, partition insulation, partitioning insulation, acoustic partition, acoustic partitions, acoustic wall, acoustic walls, ceiling insulation, ceiling cavity insulation, roof insilation, roof space insulation, roof cavity insulation, skillion insulation, skillion roof insulation, skillion cavity insulation, Snugfloor, Classic, Ultra, Masonry Wall, Retrofit, Silencer, Silencer Midfloor,

2 Clauses

2.1 Scope

Help Note:

For technical information on products to attach to this project, please visit https://productspec.co.nz/en/supplier/Pink%20Batts

2.1.1 Scope

Supply and install Pink® Batts® Insulation, as specified herein, to the locations identified on the drawings, complete with all accessories required for proper installation and performance. All aspects of this work shall be in complete accordance with Tasman Insulation technical information and installation requirements (check pinkbatts.co.nz, call 0800 746 522, or email customer@pinkbatts.co.nz for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Pink® Batts® Insulation.

Pink® Batts® insulation is certified under the GREENGUARD Certification Program (UL 2818). Being certified for indoor air quality gives an assurance that products meet strict chemical emissions limits (including minimal levels of VOCs and formaldehyde), to help create healthier indoor environments.

2.1.2 Extent of Work

The following is a list and/or general description of the extent of the Pink® Batts® Insulation works, which are more specifically defined in the contract documents, required for the completion of the contract works:

SMARTSPEC

2.2 Requirements

2.2.1 Safety

Comply with the Health and Safety at Work Act 2015 (HSWA), and with all relevant Health and Safety at Work Regulations 2016, and with all relevant WorkSafe New Zealand (WorkSafe) Approved Codes of Practice and WorkSafe Information and Guidance, particularly those for construction and building maintenance.

2.2.2 Warranty - applies to BRANZ Appraised Pink® Batts® Ceiling & Wall products

Pink® Batts® Lifetime Product Warranty:

- 50 Years Warranty for BRANZ Appraised Pink® Batts® ceiling and wall products installed according to the warranty conditions.
- Provide the Pink® Batts® Lifetime Product Warranty on the manufacturer's standard warranty form.
- Commence the warranty from the date of permanent installation.

2.2.3 Substitutions

Pink® Batts® Insulation shall be as specified herein and as indicated on the approved drawings. The substitution of Pink® Batts® branded products for alternative brands is not permitted under any circumstances.

The substitution of a specified Pink® Batts® product for an alternative Pink® Batts® branded product by the Installer (PinkFit® or other) shall only be permitted with the Contract Administrator's written authorisation, and shall be at no additional cost to the Principal. Should any resultant extra work and/or redesign work be required to accommodate alternative Pink® Batts® branded products to satisfy design, performance and compliance requirements, then the cost of these shall be borne by the Installer.

2.2.4 Inspections

Carry out all necessary pre-installation and pre-line inspections of Pink® Batts® Insulation for each area of work in accordance with the requirements of industry best practice recommendations and manufacturer guidelines.

Complete a Pre-Installation Checklist prior to installation, and a Pre-Line Checklist before handing over for subsequent work.

Note: Pink® Batts® checklist applies only to Pinkfit.

2.3 Underfloor Thermal Insulation

2.3.1 Pink® Batts® SnugFloor® R2.6 Narrow

Pink® Batts® SnugFloor® R2.6 Narrow - product code 7131451. A non-combustible, resin bonded fibrous glasswool insulation manufactured from recycled and virgin glass and cured urea extended phenolic resin. Suitable for use in timber-framed floors. R-value R-2.6. 110mm thick x 480mm wide x 1220mm long segments.