Sto Plaster Systems

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Co-operation 3
- Sample 3
- Workmanship 3
- Delivery & Handling 3
- Substrate Preparation 3
- Plaster System 8
- Control Joints 9
- Flexible Sealant 11
- Installation 11
- Substrate Primer 13
- Sheet Jointing 14
- Base Coat 14
- Meshed Waterproofing 15
- Meshed Reinforcement Coat 15
- Finishing Coat 16
- Coating 19
- Completion 20

Compliances 20

SWARTSPEC

1 Specification Details

Trade Sections: Plasterwork
Description:
Keywords: Plasterwork, STO Plaster Systems, plaster, plastering, plaster finishes, plastered cladding, plaster systems, plaster cladding systems, wall cladding plaster systems, plastered exterior wall cladding, plastered walls, wall plaster, solid plaster systems, solid plastered walls, facade plaster systems, polystyrene plaster systems, EPS plaster systems, XPS plaster systems, insulated concrete formwork plaster systems, ICF plaster systems, lightweight concrete plaster systems, light-weight concrete plaster systems, light weight concrete plaster systems, LWC plaster systems, precast concrete plaster systems, concrete plaster systems, AAC panel plaster systems, AAC block plaster systems, AAC brick plaster systems, concrete block plaster systems, concrete block masonry plaster systems, concrete blockwork plaster systems, fibre cement sheet plaster systems, fibre-cement sheet plaster systems, masonry plaster systems, masonry-work plaster systems, brickwork plaster systems, StoArmat Miral Plaster System, StoPoren Plaster System, StoLite Plaster System, StoArmat Plaster System, Stolit K Plaster System, StoEze Joint Plaster System, StoMiral Plaster System,

2 Clauses

2.1 Scope

Help Note:
This specification applies to Sto Plasters only and does not cover Sto plastered cladding systems; refer to the Sto Plastered Cladding Systems specification.

For technical information on products to attach to this project, please visit https://productspec.co.nz/en/supplier/sto

2.1.1 Scope

Supply and install the selected Sto Plaster Systems as monolithic plaster finish to the walls identified on the drawings and as noted below, complete with all components and accessories. All aspects of this work shall be in complete accordance with relevant Sto BRANZ appraised systems, Sto Plaster Systems Specifications and Installation Guides and Details (check www.sto.co.nz, or call 04 801 4749 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Sto Plaster Systems.

SMARTSPEC

2.2 Co-operation

2.2.1 Co-operation

Co-operate with other trades to ensure that all preliminary and preparatory works are completed to specification and as shown on the drawings. Co-ordinate with other trades to install Sto Plaster coats as required.

2.3 Sample

2.3.1 Sample

Submit a clearly identified 300 x 300mm sample of the selected coloured plaster finish for signed approval of the Architect/Designer; do not proceed until the sample has been approved.

2.4 Workmanship

2.4.1 Workmanship

Where required by the NZ Building Act 2004 it is the building contractor's responsibility to ensure that all restricted building work is carried out by a Licensed Building Practitioner.

All work shall be carried out to best trade practice by experienced and skilled PPCS (Proprietary Plaster Cladding Systems) Registered Tradesmen certified to apply and install Sto plasters and accessories in accordance with the Sto Plaster System Specifications and Installation Guides and Details and as shown on the drawings.

Protect all adjacent surfaces as necessary before commencing. Mask off all window and door joinery and other exposed fittings and fixtures and all glazing.
Leave all plastered surfaces clean, sound, and free from blemishes of any kind.

2.5 Delivery & Handling

2.5.1 Delivery & Handling

Store all Sto plasters, coatings and accessories under cover, keep dry and protect from damage at all times. Store uPVC mouldings on a flat and even surface out of direct sunlight. Do not use damaged, defective or contaminated materials or products, or products that are beyond the designated shelf life.
Handle Sto plasters, coatings and accessories in accordance with the manufacturer's recommendations.

2.6 Substrate Preparation

Help Note:
Select the appropriate substrate construction type.

SMARTSPEC