Polyflor Resilient Flooring

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Resilient Flooring 2
- Trim & Accessories 8
- Underlayment 10
- Levelling Patch Compounds 10
- Primers 11
- Adhesive 11
- Sample 13
- Reserve Material 13
- Co-operation 13
- Workmanship 13
- Delivery & Handling 14
- Preparation 14
- Installation 17
- Completion 20

Compliances 20

SMARTSPEC

1 Specification Details

Trade Sections: Floor Coverings
Description: Resilient Flooring – by Polyflor
Keywords: Polyflor, Floor covering, Resilient Flooring, Acoustic Flooring, Wall - Ceiling, Screed & Adhesives. Okatmos Servoplan Servofine Affinity Polyclad Finesse Polyflor Sport 67, Polysafe, Polysafe Vogue, Polysafe Verona, Quattro, Expona, Bloc, Acoustix, Palettone, Prestige, Wovon, Expona, Okatmos star 100, Okatmos star 110, Okatmos star 120, Okatmos star 150 plus, Okamul PU. vinyl

2 Clauses

2.1 Scope

Help Note:
For technical enquiries contact Polyflor on 0800765935 or e-mail sales@polyflor.co.nz or head to the website www.polyflor.co.nz

2.1.1 Scope

Supply and install the specified Commercial Vinyl Surfacing from Polyflor to the locations, layouts and details shown on the drawings, complete with all associated components and accessories. All aspects of this work shall be in complete accordance with the manufacturers' technical literature (check www.polyflor.co.nz, or call 0800 765 935 for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.
No substitutions are permitted for the specified Commercial Vinyl Surfacing from Polyflor.

2.2 Resilient Flooring

Help Note:
For technical enquiries contact Polyflor on 0800 765 935 or e-mail sales@polyflor.co.nz or head to the website www.polyflor.co.nz

2.2.1 Classic Mystique PUR

Classic Mystique PUR Heavy duty, homogeneous floor coverings.
Installed in accordance with the manufacturer's installation requirements and NZS/AS 1884, to the locations and layout shown on the drawings.
Gauge: 2mm
Wear Layer: 2mm
Roll size: 2mx20m
Tile size: 300x300mm, 608x608mm
Colour: 24 Shades
Slip resistance: DIN 51130 R9, EN 13893 DS, AS 4586 R9
Reaction to fire: EN 13501-1 Bfl – s1, ASTM E662 <450, ASTM E648 Class 1, BCA Spec CIJO Clause 3.
Underfloor heating: EN 12664-2 Suitable, max 27°C

Colour:
Installed location:

2.2.2 XL PU

XL PUR Heavy duty, homogeneous floor coverings.
Installed in accordance with the manufacturer's installation requirements and NZS/AS 1884, to the locations and layout shown on the drawings.
Gauge: 2mm
Wear Layer: 2mm
Roll size: 2mx20m
Tile size: 300x300mm, 608x608mm
Colour: 24 Shades
Slip resistance: EN 13893 DS, AS 4586 R9
Reaction to fire: EN 13501-1 Bfl – s1, ASTM E662 <450, ASTM E648 Class 1.
Underfloor heating: EN 12664-2 Suitable, max 27°C

Colour:
Installed location:

2.2.3 Palettone

Palettone Heavy duty, homogeneous, floor coverings with a polish free maintenance regime.
Installed in accordance with the manufacturer's installation requirements and NZS/AS 1884, to the locations and layout shown on the drawings.
Gauge: 2mm
Wear Layer: 2mm
Roll size: 2mx20m
Colour: 50 Shades
Slip resistance: EN 13893 DS, AS 4586 R10, DIN 51130 R10
Reaction to fire: EN 13501-1 Bfl – s1, ASTM E662 <450, ASTM E648 Class 1, AS ISO 9239-1 Class B
Underfloor heating: EN 12664-2 Suitable, max 27°C

Colour:
Installed location:

2.2.4 Forest FX PUR

Forest FX PUR is cross-linked polyurethane reinforcement, UV cured polish free maintenance regime for the lifetime of the flooring.
Installed in accordance with the manufacturer's installation requirements and NZS/AS 1884, to the locations and layout shown on the drawings.
Gauge: 2mm
Wear Layer: 0.70mm
Roll size: 2mx20m
Colour: 18 Shades
Slip resistance: EN 13893 DS (dry conditions), AS 4586 R10, DIN 51130 R10