Roofing Industries Profiled Metal Cladding

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Requirements 4
- Corrugated Cladding 6
- Trapezoidal Cladding 10
- Trough Cladding 20
- Tray Cladding 21
- European Tray Unsupported Cladding 23
- European Tray Fully-Supported Cladding 30
- Cladding Material 44
- Components & Accessories 90
- Co-operation 94
- Workmanship 94
- Delivery & Handling 95
- Preparation 95
- Cavity Battens 99
- Installation 101
- Fixing 103
- Completion 158

Compliances 159

SWIFTSPEC

1 Specification Details

Trade Sections: Roofing
Description:
Keywords: Roofing, Roofing Industries, cladding, long-run cladding, long run metal cladding, long-run metal cladding, longrun metal cladding, long-run metal wall cladding, profiled longrun cladding, profiled long-run cladding, wall cladding, profiled metal, profile metal, profiled steel, profile steel, profiled metal cladding, profile metal wall cladding,, metal cladding, prepainted cladding, pre-painted cladding, prepainted wall cladding, pre-painted wall cladding, prefinished cladding, pre-finished cladding, prefinished wall cladding, pre-finished wall cladding, precoated cladding, pre-coated cladding, precoated wall cladding, pre-coated wall cladding, prepainted steel, pre-painted steel, prefinished steel pre-finished steel, precoated steel, pre-coated steel, coated steel, prepainted metal, pre-painted metal, prefinished metal, pre-finished metal, precoated metal, pre-coated metal, coated metal, roll formed cladding, roll formed steel cladding, roll formed metal cladding, corrugated cladding, trapezoidal cladding, trough cladding, tray cladding, fully supported metal cladding, 0.4mm BMT, 0.55mm BMT, 0.48mm BMT, BMT, bmt, (BMT), base metal thickness, G550, G300, rainwater catchment, rainwater run-off, rainwater run off, run-off, run off, Colorsteel, Colorsteel Endura, Colorsteel Maxx, Colorcote, Colorcote ZM8, ZM8, ZMX, ZR8, ZRX, ARX, AR8, Zincalume, galvanised steel, zinc cladding, Zinc Quartz cladding, Zinc Anthra cladding, aluminium cladding, copper cladding, stainless steel cladding, True Oak Corrugate, Corrugate, Maxispan, Multidek, Multirib, Ribline 800, Ribline800, Ribline 960, Ribline 960, RT7, Slimline Mini Corrugate, Trimrib, Eurostyle, Eurostyle Epic Interlocking Panel, Eurostyle Epic, Eurostyle Spanlok, Eurostyle Eurolok, interlocking wall & soffit panel, European tray unsupported cladding, European tray fully-supported cladding, standing seam, angle seam, roll seam, roll cap, snaplock,

2 Clauses

2.1 Scope

Help Note:

Select the appropriate Environmental Category in which the project is situated:

- C2 Low: Characterised by no obvious marine or industrial influences. Typically more than 1000 metres from the exposed coasts, or more than 500 metres from industrial emissions.
- C3 Medium: Characterised by little or no salt deposits; the occasional smell of salt in the air. Typically 500-1,000 metres from breaking surf such as found on exposed coasts, OR in the immediate vicinity of calm salt water such as estuaries.
- C4 High: Characterised by light salt deposits; a frequent smell of salt in the air. Typically starts 100-

500 metres from breaking surf such as found on exposed coasts; in the immediate vicinity of large expances of calm salt water such as harbour foreshores. This environment may be extended inland by prevailing winds and local conditions.
- C5M Very High - Marine, Geothermal: Characterised by heavy salt deposits; the almost constant smell of salt spray in the air; close to breaking surf (typically 50-100 metres) such as found on exposed coasts; this environment may be extended inland by prevailing winds and local conditions. Typically 50 metres from high water on East Coast, 100 metres from high water on West Coast.
- C5I Very High - Industrial: Characterised by industrial areas with high humidity and aggressive atmospheres.

For further information and technical advice, call Roofing Industries on 0800 844 822, or email office@roof.co.nz.

For technical information on products to attach to this project, please visit https://productspec.co.nz/en/supplier/roofing industries

2.1.1 ISO 9223 Category C2 Low (Inland Moderate)

Supply and install the specified Profiled Metal Cladding from Roofing Industries to the locations and orientations identified on the drawings, complete with all components and accessories required for proper installation and performance. All aspects of this work shall be in complete accordance with the Roofing Industries Profile Technical Summary and the NZMRM Code of Practice (check www.roof.co.nz, call 0800 844 822, or email office@roof.co.nz for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Roofing Industries Profiled Metal Cladding.

2.1.2 ISO 9223 Category C3 Medium (Coastal Moderate)

Supply and install the specified Profiled Metal Cladding from Roofing Industries to the locations and orientations identified on the drawings, complete with all components and accessories required for proper installation and performance. All aspects of this work shall be in complete accordance with the Roofing Industries Profile Technical Summary and the NZMRM Code of Practice (check www.roof.co.nz, call 0800 844 822, or email office@roof.co.nz for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Roofing Industries Profiled Metal Cladding.

2.1.3 ISO 9223 Category C4 High (Coastal Severe)

Supply and install the specified Profiled Metal Cladding from Roofing Industries to the locations and orientations identified on the drawings, complete with all components and accessories required for proper installation and performance. All aspects of this work shall be in complete accordance with the Roofing Industries Profile Technical Summary and the NZMRM Code of Practice (check www.roof.co.nz, call 0800 844 822, or email office@roof.co.nz for the latest editions), other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for Roofing Industries Profiled Metal Cladding.