Mammoth Polyester Insulation

TABLE OF CONTENTS

Specification Details 2
Clauses 2
- Scope 2
- Underfloor Thermal Insulation 3
- Wall Thermal Insulation 6
- Ceiling Thermal Insulation 10
- Skillion Roof Thermal Insulation 12
- Acoustic Insulation 13
- Acoustic Baffle 16
- Acoustic Panel 16
- Co-operation 17
- Delivery & Handling 18
- Workmanship 18
- Installation 18
- Completion 22

Compliances 23

SWARTSPEC

1 Specification Details

Trade Sections: Insulation
Description:
Keywords: Insulation, InsulPro, Mammoth Residential Insulation, residential insulation, Mammoth, thermal insulation, acoustic insulation, thermally bonded polyester insulation, non-woven polyester fibre insulation, polyester insulation, polyester fibre insulation, polyester thermal insulation, polyester acoustic insulation, polyester blanket, polyester pads, blanket, insulation blanket, thermal insulation blanket, thermal blanket, thermal insulating blanket, pads, insulation pads, thermal insulation pads, thermal pads, insulating pads, thermal insulating pads, acoustic blanket, acoustic pads, acoustic insulation blanket, acoustic insulation pads, acoustic insulating blanket, acoustic insulating pads, acoustic panels, insulating panels, acoustic insulation panels, thermal envelope insulation, envelope insulation, cavity insulation, under floor insulation, floor insulation, floor cavity insulation, interfloor insulation, inter-floor insulation, interstorey insulation, inter-storey insulation, wall insulation, wall cavity insulation, external wall insulation, internal wall insulation, partition insulation, partitioning insulation, acoustic partition, acoustic partitions, acoustic wall, acoustic walls, ceiling insulation, ceiling cavity insulation, roof insilation, roof space insulation, roof cavity insulation, skillion insulation, skillion roof insulation, skillion cavity insulation, ceiling baffle, baffle stack, acoustic baffle, acoustic baffle stack, acoustic block, sound block, R-value, R1.8, R1.9, R2.0, R2.2, R2.5, R2.6, R2.9, R3.2, R3.6, Mammoth Multi, Multi, Mammoth Wall, Mammoth Skillion, Mammoth 900,

2 Clauses

2.1 Scope

Help Note:
For technical information on products to attach to this project, please visit productspec.co.nz/en/supplier/mammoth%20insulation.

2.1.1 Scope

Supply and install the specified Mammoth® Polyester Insulation products to the locations as identified on the drawings, complete with accessories. All aspects of this work shall be in complete accordance with Mammoth Insulation product manuals and installation guides, (check www.mammoth.co.nz, or call 0800 626 668 for the latest editions), relevant BRANZ Appraisals, other relevant product manufacturers' recommendations, and as shown on the drawings.

No substitutions are permitted for the specified Mammoth Polyester Insulation products.

SWEETSPEC

2.2 Underfloor Thermal Insulation

Help Note:
Insulation is listed in order of R-value - low value to high value.

2.2.1 Mammoth Underfloor Sections R1.9 - 90mm thick, 370mm x 1140mm

Mammoth Underfloor Sections R1.9 - 90mm thick, 370mm x 1140mm
Friction fit airlay insulation sections made from non-woven thermally bonded polyester fibre, coloured white. Installed as underfloor thermal insulation to the locations shown on the drawings in accordance with the manufacturer's requirements and BRANZ Appraisal No.802. R-value R1.9. 90mm thick x 370mm wide x 1140mm long sections. Can be double layered to meet Building Code.

Location:

2.2.2 Mammoth Underfloor Sections R1.9 - 90mm thick, 425mm x 1140mm

Mammoth Underfloor Sections R1.9 - 90mm thick, 425mm x 1140mm
Friction fit airlay insulation sections made from non-woven thermally bonded polyester fibre, coloured white. Installed as underfloor thermal insulation to the locations shown on the drawings in accordance with the manufacturer's requirements and BRANZ Appraisal No.802. R-value R1.9. 90mm thick x 580mm wide x 1140mm long sections. Can be double layered to meet Building Code. Can be double layered to meet Building Code

Location:

2.2.3 Mammoth Underfloor Sections R1.9 - 90mm thick, 475mm x 1140mm

Mammoth Underfloor Sections R1.9 - 90mm thick, 475mm x 1140mm
Friction fit airlay insulation sections made from non-woven thermally bonded polyester fibre, coloured white. Installed as underfloor thermal insulation to the locations shown on the drawings in accordance with the manufacturer's requirements and BRANZ Appraisal No.802. R-value R1.9. 90mm thick x 580mm wide x 1140mm long sections. Can be double layered to meet Building Code.

Location:

2.2.4 Mammoth Underfloor Section R1.9 - 90mm thick, 580mm x 1140mm

Mammoth Underfloor Section R1.9 - 90mm thick, 580mm x 1140mm
Friction fit airlay insulation sections made from non-woven thermally bonded polyester fibre, coloured white. Installed as underfloor thermal insulation to the locations shown on the drawings in accordance with the manufacturer's requirements and BRANZ Appraisal No.802. R-value R1.9. 90mm thick x 580mm wide x 1140mm long sections. Can be double layered to meet Building Code.

Location:

2.2.5 Mammoth Underfloor Sections R2.8 - 140mm thick, 370mm x 1140mm

Mammoth Underfloor Sections R2.8 - 140mm thick, 370mm x 1140mm
Friction fit airlay insulation sections made from non-woven thermally bonded polyester fibre,

SMARTSPEC